

4 Early Life Factor Prediction for Devices

4.1 Early Life Factor for Device with Limited or No Burn-In	4-1
4.2 Early Life Factor for Device with Extensive Burn-In	4-1
4.2.1 Equivalent Operating Time for Burn-in	4-1
4.2.2 Early Life Factor	4-2
4.3 Examples	4-2
4.3.1 Example 1: Limited or No Burn-In	4-2
4.3.2 Example 2: Extensive Burn-In	4-3

5 Failure Rate Prediction for Units

5.1 Method I: Unit Steady-State Failure Rate Using the Parts Count Method	5-1
5.2 Method II: Integrating Laboratory Test Data on Units	5-3
5.2.1 When Laboratory Test Units Have No Previous Unit/Device Burn-In . . .	5-3
5.2.2 When Laboratory Test Units Had Previous Burn-in	5-4
5.3 Method III: Integrating Field Data on Units	5-5
5.3.1 Total Operating Hours	5-6
5.3.2 Adjustment Factor (V)	5-6
5.4 Unit Early Life Factor	5-7
5.5 Sampling Method - Using Default Temperature and Stress Factors on a Sample of Units	5-7
5.6 Examples	5-8
5.6.1 Example 1: Method I, Parts Count Prediction	5-9
5.6.2 Example 2: Early Life Factor	5-9
5.6.3 Example 3: Method II, Integrating Laboratory Test Data	5-10
5.6.3.1 Example 3a: No Previous Burn-In of Laboratory Test Units	5-10
5.6.3.2 Example 3b: Previous Burn-In of Laboratory Test Units	5-10
5.6.4 Example 4: Method III, Integrating Field Test Data	5-11
5.6.4.1 Example 4a: Subject Unit and Test Unit are Identical and Operated Under the Same Conditions	5-11
5.6.4.2 Example 4b: Subject Unit and Test Unit are Identical but Operated in Different Environments	5-12
5.6.4.3 Example 4c: Test Unit Is Similar but Not Identical to Subject Unit	5-12
5.6.5 Example 5: Method I, Parts Count Prediction, Devices Within a Device Type Have Different Operating Temperatures	5-12

6 System Reliability (Service Affecting Reliability Data)

6.1 Serial System Reliability	6-1
6.1.1 Steady-State Failure Rate	6-1
6.1.2 Early Life Factor	6-1
6.2 Non-Serial Systems	6-2

7 Upper Confidence Levels for Failure Rates

7.1 Upper Confidence Level Calculation	7-1
7.2 Examples	7-2
7.2.1 Example 1: 90% Upper Confidence Level of the Steady-State Failure Rate	7-2
7.2.2 Example 2: 90% Upper Confidence Level of the Early Life Failure Rate	7-2

8 Device Parameter Values

8.1 Capacitor Parameter Values	8-2
8.2 Connector Parameter Values	8-3
8.3 Diode Parameter Values	8-4
8.4 Inductor Parameter Values	8-5
8.5 Integrated Circuit Parameter Values	8-6
8.5.1 Analog Integrated Circuit Devices	8-7
8.5.2 Digital Integrated Circuit Devices	8-8
8.5.3 Random Access Memory (RAM)	8-10
8.5.4 Read Only Memory (ROMS, PROMS, EPROMS)	8-12
8.5.5 Microprocessor	8-14
8.5.6 Microcontroller	8-15
8.5.7 Hybrid Microcircuits	8-15
8.5.8 Combined Analog-Digital Integrated Circuit (Gate Array and Program Array Logic)	8-16
8.6 Microwave Element Devices	8-17
8.7 Opto-Electronic Device Parameter Values	8-18
8.7.1 Fiber Optic Communication Devices and Modules	8-18
8.7.2 Other Opto-Electronic Devices	8-20
8.8 Relay Parameter Values	8-21
8.9 Resistor Parameter Values	8-22
8.9.1 Fixed Resistor	8-22
8.9.2 Variable Resistor	8-23
8.9.3 Resistor Networks	8-24
8.10 Switch Parameter Values	8-25
8.11 Thermistor Parameter Values	8-26
8.12 Transistor Failure Rates	8-27
8.13 Rotating and Miscellaneous Device Parameter Values	8-29

9 Failure Rate Factors

9.1 Temperature Factor	9-1
9.2 Electrical Stress Factor	9-3
9.2.1 Electrical Stress Curves	9-3
9.2.2 Electrical Stress Percentage	9-4
9.3 Quality Factor	9-6
9.4 Environment Factor	9-8

Appendix A: Failure Rate Units

Appendix B: References

B.1 Telcordia Documents	B-1
B.2 Non-Telcordia Documents	B-1
B.3 Documents on Derating	B-1
B.4 Telcordia Documents Referencing SR-332 or a Predecessor	B-2
B.5 Reference Notes	B-6
B.6 Contact Customer Service	B-6
B.7 Order Documents Online From the Telcordia SuperStore	B-6
B.8 Web Sites for Generic Requirements Information	B-7
B.9 Licensing Agreements for Telcordia Documents	B-7

Appendix C: Glossary

C.1 Acronyms C-1
C.2 Definition of Terms C-3

List of Figures

Figure 2-1 Bathtub Curve 2–4

List of Tables

Table 1-1	Participants in the Development of SR-332, Issue 4	1-3
Table 8-1	Capacitor Failure Rate Parameters	8-2
Table 8-2	Connector Failure Rate Parameters	8-3
Table 8-3	Diode Failure Rate Parameters*	8-4
Table 8-4	Inductor Failure Rate Parameters	8-5
Table 8-5	Analog Integrated Circuit Failure Rates	8-7
Table 8-6	Digital Integrated Circuit Failure Rate Parameters	8-8
Table 8-7	Digital Integrated Circuit Failure Rates	8-9
Table 8-8	Random Access Memory Failure Rate Parameters	8-10
Table 8-9	Static Random Access Memory (SRAM) Failure Rates	8-11
Table 8-10	Dynamic Random Access Memory (DRAM) Failure Rates	8-12
Table 8-11	Read Only Memory Failure Rate Parameters	8-13
Table 8-12	Read Only Memory Failure Rates	8-13
Table 8-13	Microprocessor Failure Rate Parameters	8-14
Table 8-14	Bipolar and NMOS Microprocessor Failure Rates	8-14
Table 8-15	CMOS Microprocessor Failure Rates	8-15
Table 8-16	Microwave Element Device Failure Rate Parameters	8-17
Table 8-17	Fiber Optic Communication Device/Module Failure Rate Parameters	8-18
Table 8-18	Opto-Electronic Device Failure Rate Parameters	8-20
Table 8-19	Relay Failure Rate Parameters	8-21
Table 8-20	Fixed Resistor Failure Rate Parameters	8-22
Table 8-21	Variable Resistor Failure Rate Parameters	8-23
Table 8-22	Resistor Network Failure Rate Parameters	8-24
Table 8-23	Switch Failure Rate Parameters	8-25
Table 8-24	Thermistor Failure Rate Parameters	8-26
Table 8-25	Transistor Failure Rate Parameters	8-27
Table 8-26	Miscellaneous Device Failure Rate Parameters	8-29
Table 8-27	Rotating and Miscellaneous Device Failure Rate Parameters	8-30
Table 9-1	Temperature Factors πT	9-2
Table 9-2	Electrical Stress Factors π_S	9-4
Table 9-3	Guidelines for Determination of Electrical Stress Percentage	9-5
Table 9-4	Device Quality Level Description and Factor π_Q	9-7
Table 9-5	Environmental Conditions and Multiplier Factors (π_E)	9-8
Table A-1	Reliability Conversion Factor	A-1